

H-200M SERIES™

WATER CONDITIONING SYSTEM



System Applications

- Agriculture
- Apartment Buildings
- Boiler Water Treatment
- Car Washes
- Commercial Buildings
- Condominiums
- Dairies
- Factories
- Hospitals
- Homes
- Laundries
- Mobile Home Parks
- Motels and Hotels
- Nursing and Rest Homes
- Office Buildings
- Restaurants
- Schools

The H200M Control is User Friendly and Reliable.

- Modular Design
- Non-Corrosive Internals
- Lead Free Brass Valve¹
- One Piece Stack Assembly
- Piston Operated
- Disassemble and Reassemble in Minutes

¹H200M Valve Bodies have an NSF Approved Food Grade Electro-Deposited Epoxy Coating to Protect Against Corrosion


Hellenbrand[®]
What's In Your Water?[™]

H-200M SERIES™

WATER CONDITIONING SYSTEM



Going Green

Brine Reclaim – The H200M standard electronic package is capable of reclaiming up to 30% of the salt used in regeneration for the next regeneration. Salt savings will vary depending on the lbs. of salt per cubic foot of resin used to regenerate. A brine reclaim kit is required for this option.

Water Reclaim – The H200M standard electronic package is capable of reclaiming much of the water used to regenerate the water softener and re-use that water to flush toilets. This water is typically soft and is free of the salt/brine discharge which is diverted to your standard drain/waste system. A water reclaim kit is required for this option.

H200M Features and Benefits

- 2.0" Inlet & Outlet provides higher service flows with less pressure drop
- 12-Volt Operation AC or DC
- Electronic Meter Demand with Calendar Day Override
- Scrolling User Screen shows capacity remaining, time of day and flow rate
- 12-Volt Relay Driver allows multiple dry contact signals
- Service Interval Screen reminds you to call for preventative maintenance service
- Differential Pressure Switch Capability
- Fully Programmable Cycle Position and Times
- Nine Cycle Control
- Soft Water Brine Tank Re-Fill
- Multiple Backwash and Rinse Capabilities
- Quiet Operation
- Variable Reserve automatically adjusts to changing water usage patterns.
- Several programming options including: variable reserve, fixed reserve, calendar day override, delayed or immediate regeneration.
- Diagnostics
 - Days since last regeneration
 - Gallons since last regeneration
 - Gallon reserve capacity last 7 days
 - 63 Days history of daily totals usage
 - Maximum flow rate for the last seven days
 - Total number of regenerations
 - Total days in service
 - Total gallons processed
- Permanent memory backup of all programming
- 2-1/2 years Time of Day Backup
- Uses less than \$2 of electricity per year

System Designs Options

- Single
- Parallel Operation
- Twin Alternating
- Demand Recall - Up to six units
- No Raw Water Bypass
- Alternate Source Regeneration

Meter Accuracy

- 1.5" Meter 0.5 – 75 gpm
- 2" Meter 1.5 – 150 gpm
- Accuracy: ±5%

Specifications

| DEMAND MODEL NAME | MINERAL CU. FT. | LOW SALT GRAINS/LBS. | CAPACITY MED. SALT GRAINS/LBS. | HIGH SALT GRAINS/LBS. | FLOW RATE @ 15 PSI | PEAK FLOW RATE @ 25 PSI | BACK WASH RATE GPM | MINERAL TANK (INCHES) | BRINE TANK ¹ | |
|-------------------|-----------------|----------------------|--------------------------------|-----------------------|--------------------|-------------------------|--------------------|-----------------------|-------------------------|-----------------------|
| | | | | | | | | | TANK SIZE (INCHES) | SALT STORAGE (POUNDS) |
| H200M-60 | 2 | 38,000/12 | 56,000/20 | 64,000/30 | 38 | 49 | 4.2 | 13x54 | 18x40 | 330 |
| H200M-90 | 3 | 57,000/18 | 84,000/30 | 96,000/45 | 39 | 50 | 4.2 | 14x65 | 18x40 | 300 |
| H200M-120 | 4 | 76,000/24 | 112,000/40 | 128,000/60 | 47 | 60 | 5.3 | 16x65 | 24x41 | 640 |
| H200M-150 | 5 | 95,000/30 | 140,000/50 | 160,000/75 | 53 | 69 | 7.5 | 18x65 | 24x50 | 750 |
| H200M-150-21 | 5 | 95,000/30 | 140,000/50 | 160,000/75 | 72 | 94 | 9.0 | 21x62 | 24x50 | 750 |
| H200M-180 | 6 | 114,000/36 | 168,000/60 | 192,000/90 | 51 | 66 | 7.5 | 18x65 | 24x50 | 750 |
| H200M-180-21 | 6 | 114,000/36 | 168,000/60 | 192,000/90 | 70 | 91 | 9.0 | 21x62 | 24x50 | 750 |
| H200M-210 | 7 | 133,000/42 | 196,000/70 | 224,000/105 | 66 | 85 | 9.0 | 21x62 | 24x50 | 710 |
| H200M-240 | 8 | 152,000/48 | 224,000/80 | 256,000/120 | 76 | 98 | 13.0 | 24x72 | 24x50 | 680 |
| H200M-270 | 9 | 171,000/54 | 252,000/90 | 288,000/135 | 74 | 96 | 13.0 | 24x72 | 24x50 | 678 |
| H200M-300 | 10 | 190,000/60 | 280,000/100 | 320,000/150 | 73 | 94 | 13.0 | 24x72 | 24x50 | 641 |
| H200M-300-30 | 10 | 190,000/60 | 280,000/100 | 320,000/150 | 89 | 115 | 20.0 | 30x72 | 24x50 | 641 |
| H200M-450 | 15 | 285,000/90 | 420,000/150 | 480,000/225 | 84 | 109 | 20.0 | 30x72 | 30x50 | 1259 |
| H200M-600 | 20 | 380,000/120 | 560,000/200 | 640,000/300 | 93 | 119 | 30.0 | 36x72 | 39x48 | 1640 |
| H200M-750 | 25 | 475,000/150 | 700,000/250 | 800,000/375 | 98 | 127 | 40.0 | 42x72 | 42x60 | 2580 |
| H200M-900 | 30 | 570,000/180 | 840,000/300 | 960,000/450 | 96 | 120 | 40.0 | 42x72 | 50x60 | 4130 |
| H200M-1200 | 40 | 760,000/240 | 1,120,000/400 | 1,128,000/600 | 98 | 127 | 50.0 | 48x72 | 50x60 | 3940 |

¹Suggested brine tank size with grid plate option.

Product improvement designs are subject to change without notice.

Refer to Hellenbrand Bulletin 2050 "Flow Rates and Soft Water Quality (Hardness Leakage) if your application requires that levels of hardness leakage do not exceed "x".



Hellenbrand, Inc.
404 Moravian Valley Road
Waunakee, WI 53597
www.hellenbrand.com

DEALER NAME:

